

Your Solution Partner in Energy

ALMSD 1100

Diesel Generating Sets

alimar
GENERATOR



Prime Power

Refers to the main power supply, working under 70% average load for unlimited time. 10% overloading is allowed.

Stand-by Power

Refers to the back up power supplied to the varying load for a limited time. Overloading is not allowed.

Generator

		Prime	Stand-by
Power (kVA)	kVA	1000	1100
Power kW	kW	800	880

Generator Model:	ALMSD 1100
Engine Manufacturer Model:	Sdec / 6WTAA 5 G31
Fuel Type:	Diesel
Frequency:	50 Hz
Power Factor:	Cos Φ = 0.8
Voltage:	400/231 V

Dimensions		With Canopy	Open Skid
Length	mm	5000	4400
Height	mm	3470	2550
Width	mm	2250	2050
Weight	kg	9350	7635
Fuel Tank Capacity	lt	H 2000	H 2000

H: External

K: Container

TBA: To be added

alimar
GENERATOR

(+98) 21 9101 27 37

www.mahantechin.com



ALMSD 1100

Diesel Generating Sets



Engine

Engine Manufacturer:	SDEC
Engine Model:	6WTAA35 G31
Engine Type:	4 Stroke Diesel Engine
Engine Stand-by Power:	kWm 970
Engine Prime Power:	kWm 882
Cylinder Arrangement:	6L
Displacement:	lt 35,1
Cooling System:	Water Cooler
Bore x Stroke:	mm 186 x 215
Compression Ratio:	15:1
Aspiration:	Turbocharger, Intercooler
Governor Type:	Electronic
Electrical System:	VDC 24
Lubricant Oil Capacity:	lt 100
Coolant Capacity:	Lt TBD
Frequency Lt:	Hz - rpm 50 - 1500
Jacket Water Heater:	Piece x W
Battery:	Piece x AH
Charge Alternator Current:	A 55
Injection System:	Direct
Cooling Air Flow:	m ³ /min TBD
Combustion Air Flow:	m ³ /min 64,9
Exhaust Gas Flow:	m ³ /min 162,6
Exhaust Gas Temperature:	°C 650
Fuel Consumption Under 100% Load:	lt/h 188,1
Fuel Consumption Under 75% Load:	lt/h 136,6
Fuel Consumption Under 50% Load:	lt/h 92,9

Alternator

Phase / Pole Number:	3/4+
Excitation System:	Self Excited, Brushless
Voltage Regulator:	A.V.R. (Automatic)
Voltage Regulation:	±%1
Insulation Class:	H
Protection Class:	IP23
Connection Type:	Star
Frequency:	Hz 50
Power Factor:	Cos Φ = 0,8
Total Harmonic Distortion (No Load):	< % 3.5
Output Voltage:	VAC 231/400

TBA: To be added

ALMSD 1100

Diesel Generating Sets

alimar
GENERATOR



Control Panel



ALM929

Alimar ALM-929 Automatic Control Module

AMF function
ATS function
Remote start function
Manual start function
Engine control function
Suitable for remote monitoring

Mains and Genset LL- LN Voltages

Mains and generator frequency
Mains and genset phase currents
Mains and generator neutral currents
Grid and generator phase and total, kW, kVA, kVAR
Power factor, engine speed, battery voltage and more

Connections

3 phase 4 wire, stars & delta
3 phase 3 wire, 2 current transformer
2 phase 3 wire
1 phase 2 wire

Communication

RS232 - 485 connection with cable
J1939-CANBUS
GSM / GPRS connection
Ethernet connection
Modbus RTU



AMF9

Protection Functions

- Overvoltage
- Low voltage
- Voltage asymmetry and phase sequence
- High frequency
- Low frequency
- Short-circuit current
- Overcurrent
- Power factor
- Coolant temperature
- Low oil pressure

Auto Panel Features

- Automatic generator, grid control and fault monitoring
- Easy control with a user-friendly interface from the panel screen
- Remote operation with optional communication cards
- Manual programming with password-protected service interface
- Manual control of generator and transfer panel with buttons on the front panel
- Front panel protection class IP65
- With an operating temperature of -20 C to +70 C and a storage temperature of -40 C to +80 C

ALMSD 1100

Diesel Generating Sets

Standard Features

Engine

Low fuel consumption and high performance latest technology diesel engines are used with electronic or mechanical governor, water-cooled radiator system, replaceable oil, fuel, air filters.

Alternator

With its robust and compact structure, steel body, maintenance-free single bearing system, brushless, self-excited system and electronic type AVR, alternators suitable for the special needs of different applications are used.

Gen-Set Canopy

Modular cabinets are used in accordance with 2000/14/EC directives, covered with sound and heat insulation flame-resistant sponge, corrosion and rust resistant paint, locks and hinges, large lockable doors on both sides for easy service and maintenance. Exhaust and silencer insulated according to engine suitability. Small and medium power fuel tank is designed as underchassis. Lifting ears on chassis. Vibration prevention wedges are used under the chassis.

Standard Accessories

- Industrial silencer and stainless steel compensator
- Maintenance-free lead-acid starter battery, cable and stand
- Jacket water heater with thermostat
- Automatic control module
- SMPS battery charger
- Relays and fuses
- Emergency stop button

Optional Features

- Remote radiator
- Coolant level sensor
- Fuel level sensor
- Winding dehumidifier heater
- Winding and bearing temperature sensors
- MCCB
- PMG/AREP

Other Accessories

- Electronic/Manual oil drain pump
- Critical type silencer
- Trailer
- Main fuel tank stainless and insulated
- Automatic transfer panel
- Spring loaded seismic isolator
- Oil and fuel tank heater
- Maintenance tools and kits

Cabin: Alimar Generator cabins are user-friendly. It provides easy maintenance and repair. Cabin monitoring the control module from outside and emergency stop button can be accessed. The inner surface of the cabinets is sound and high intensity flame that provides heat insulation does not walk covered with sponge. Cabin paint is resistant to corrosion and rust. It is resistant to. Muffler hardware on certain models hidden inside the cabin.

